



<b>Category</b>	Battens and Weatherproofs
<b>Application</b>	Ancillary, Commercial, Industrial
<b>Specification</b>	Performance

# NouLine

NouLine Batten 1800mm CCT Self-Test Emergency

**Code:** ANOU6/2/SM3



## PRODUCT FEATURES

- High performance LED batten suitable for industrial applications and ancillary areas
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Push fit terminals for ease and speed of installation
- Non-dimmable
- High efficiency up to 140lm/W
- Instant light output with unlimited switching
- Multiple conduit entry and BESA fixing points

### GENERAL INFORMATION

<b>Wattage</b>	50W/35W
<b>Lumens Delivered</b>	4900lm - 6900lm (4000K)
<b>Lm/W</b>	140lm/W
<b>Beam Angle</b>	110/150
<b>CRI</b>	80
<b>CCT</b>	3000K/4000K/6500K
<b>Input</b>	220-240V
<b>Operating Temp</b>	0°C to 30°C
<b>SDCM</b>	3
<b>Product Weight without Packaging</b>	1.48 kg

### TECHNICAL INFORMATION

<b>Light Source</b>	LED
<b>Colour / Finish</b>	White
<b>IP Rating</b>	IP20
<b>Class Protection</b>	1
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Ceiling, Suspended
<b>Lumen Depreciation</b>	L70 54,000h
<b>Warranty (Years)</b>	5
<b>CE Mark</b>	Yes
<b>Emergency Output Duration</b>	3 Hr





<b>Category</b>	Battens and Weatherproofs
<b>Application</b>	Ancillary, Commercial, Industrial
<b>Specification</b>	Performance

# NouLine

NouLine Batten 1800mm CCT Self-Test Emergency  
Code: ANOU6/2/SM3

