

Luminaires | Downlights

Slim-FitCS™ 9W IP44 Colour Switchable Low Profile Downlight

AU-PL09CS



Photometrics

Wattage	9
Lumens	870
Lm/W	97
Lumens in EM Mode	210
Beam Angle	120
Colour Temperature	3000 / 4000 / 6500
Ra	650
SDCM	5
UGR19	NO

Product Features

Brand	Aurora
IP Rating	IP44
IK Rating	IK06
L70 Hours	L80 50,000
Lifetime Class	L80
SKU Type	Non Dim
Dimmable	NO

Warranty	5
Onsite Warranty	3
Country of Origin	CN

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.9
Surge Protection (kV)	0.5
Protection Class	CLASS TWO
Fire Protection	NO
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	NO

Physical Attributes

Height (mm)	22
Overall Diameter (mm)	145
Lamp Base	LES
Cutout Diameter Min. (mm)	132
Cutout Diameter Max. (mm)	135
Mount Options	RECESSED
Finish Colour	White

Features

Marketing Feature 1	Colour switchable between 3000/4000/6500K
Marketing Feature 2	Edge-lit low profile ideal for installations with
Marketing Feature 3	Dimmable drivers available purchase separately
Marketing Feature 4	IP44 rated
Marketing Feature 5	TP(a) rated
Marketing Feature 6	L80 50,0000hrs

Marketing Feature 7

5 year warranty

Marketing Feature 8

3 year on-site warranty