

## Luminaires | Downlights

# Slim-FitCS™ 12W IP44 Colour Switchable Low Profile Downlight

AU-PL12CS



## Photometrics

<b>Wattage</b>	12
<b>Lumens</b>	1320
<b>Lm/W</b>	110
<b>Lumens in EM Mode</b>	250
<b>Beam Angle</b>	120
<b>Colour Temperature</b>	3000 / 4000 / 6500
<b>Ra</b>	650
<b>UGR19</b>	NO

## Product Features

<b>Brand</b>	Aurora
<b>IP Rating</b>	IP44
<b>IK Rating</b>	IK06
<b>L70 Hours</b>	L80 50,000
<b>Lifetime Class</b>	L80
<b>SKU Type</b>	Non Dim
<b>Dimmable</b>	NO
<b>0-10V Dimming?</b>	NO

<b>DALI Dimming?</b>	NO
<b>1-10V Dimming?</b>	NO
<b>DALI-2 Dimming?</b>	NO
<b>DMX Dimming?</b>	NO
<b>DSI Dimming?</b>	NO
<b>Warranty</b>	5
<b>Onsite Warranty</b>	3
<b>Country of Origin</b>	CN

## Electrical Specification

<b>Input Voltage (Min)</b>	220
<b>Input Voltage (Max)</b>	240
<b>Input Voltage Type</b>	AC
<b>Power Factor</b>	0.9
<b>Surge Protection (kV)</b>	0.5
<b>Inrush Current (A)</b>	8
<b>Protection Class</b>	CLASS TWO
<b>Fire Protection</b>	NO
<b>Frequency (Min) Hz.</b>	50
<b>Frequency (Max) Hz.</b>	60
<b>Operating Temp. (Max) °C</b>	40
<b>Glow Wire Test (°C)</b>	NO

## Physical Attributes

<b>Height (mm)</b>	22
<b>Overall Diameter (mm)</b>	170
<b>Lamp Base</b>	LED
<b>Cutout Diameter Min. (mm)</b>	157
<b>Cutout Diameter Max. (mm)</b>	157
<b>Mount Options</b>	RECESSED
<b>Finish Colour</b>	White

## Features

<b>Marketing Feature 1</b>	Colour switchable between 3000/4000/6500K
<b>Marketing Feature 2</b>	Edge-lit low profile ideal for installations with shallow ceilings
<b>Marketing Feature 3</b>	Dimmable drivers available purchase separately
<b>Marketing Feature 4</b>	IP44 rated
<b>Marketing Feature 5</b>	TP(a) rated
<b>Marketing Feature 6</b>	L80 50,0000hrs
<b>Marketing Feature 7</b>	5 year warranty
<b>Marketing Feature 8</b>	3 year on-site warranty